

Stationary outdoor basketball stands



Tin Shui Wah Area, Hong Kong



Fixed double-upright

Heavy duty double-upright construction consisting of \varnothing 152,4mm round tube uprights, wall thickness 4mm, placed into \varnothing 168,4 x 4,5mm ground sockets. Welded projection frame made of square tubes 50 x 50 x 2mm and 30 x 30 x 2mm. To ensure lateral stability, a supporting frame is placed between the protruding yokes. Fully galvanized. Inclusive of fibreglass backboard 180 x 105cm with wooden core, dunk ring and polyethylene net.

1. Projection 165cm. Per unit.
Article: S6.S1607

Projection 225cm. Per unit.
Article: S6.S1608

Projection 325cm. Per unit.
Article: S6.S1609

2. Paint finish after galvanisation supplement. Per unit.
Article: S6.S1610

Fixed single-upright

Heavy duty square tubular metal upright 100 x 100mm, wall thickness 5mm. The upright is placed in a floor socket with welded flanges. Fully galvanized. Inclusive of fibreglass backboard 180 x 105cm with wooden core, fixed ring and polyethylene net.

Projection 165cm. Per unit.
Article: S6.S1603

3. Projection 225cm. Per unit.
Article: S6.S1605

Paint finish after galvanisation supplement. Per unit.
Article: S6.S1611

Protection pad

200cm high x 3cm thick soft foam body with nylon-vinyl envelope cover. Easy and quick mounting with velcro straps. Standard colour blue, other colours available on request. Per unit.
Article: S6.S7815

Stationary outdoor basketball stands

1. Vandal-proof

super heavy duty backstop

Galvanized 140 x 140 x 4mm single column with floor anchor to be cast in, enamelled steel backboard 180 x 105cm, double ring without net. Backboard projection 165cm. Per unit.

Article: S6.S1630

2. Vandal-proof

super heavy duty backstop

Same as S6.S1630 but backboard projection 225cm. Per unit.

Article: S6.S1631

3. Anti-vandal fixed outdoor basketball stand -ECONOMIC- load test 500kg

Monotubular steel upright 90 x 90mm, wall thickness 3mm, hot dip galvanized, reinforced fixing plate for ring and backboard, st-steel fixing hardware.

Upright to be concreted 40cm straight into the ground or with ground sleeve.

Projection of backboard 60cm.

Ring height 305cm. Stand includes fan-shaped fibreglass backboard and ø 20mm steel ring on 6mm strong rear plate.

Article: S6.S1624

4. Same as S6.S1624 but ring height 260cm.

Article: S6.S1625

5. Ring height 305cm. Stand includes 4 ply reinforced metal backboard 1200 x 900 x 4mm, aluminium plasticised, perforated target zone and ø 20mm steel ring on 6mm strong rear plate.

Article: S6.S1626

6. Same as S6.S1626 but ring height 260cm.

Article: S6.S1627

Ground sleeve.

Article: S6.S1628

Supplement for enamelling stand after galvanization. Standard colour white.

Article: S6.S1629

