

## Multi-purpose indoor sports flooring



Fixed permanent installation, bamboo flooring

### Portable bamboo basketball floor

Article: S6.S2086 Price on demand

Fixed floor upon request.

Dimensions:

- Length: 32.5m
- Width: 19.10m
- Thickness: 30mm (rubber underlay included)

The floor consists of panels with the following dimensions: length 1.19m – width 0.92m. The panels are constructed with a toplayer of 15mm bamboo strips with continuous tongue and groove. The strips are attached to a first grade 10mm birch plywood (nailed and glued).

The underside of the panel is provided with the patented locking system. This locking system consists of a galvanized steel member and a P.E. strip.

These members are attached to the underside of the panels by means of cross recessed countersunk head screws.

The steel member consists of a steel strip (30 x 10mm) with 2 semi-circular segments (dia. 8mm) welded on. These segments fit in the semi-circular cut-outs (recesses) in the P.E. counter-part.

These segments can also be used as transport handle when installing and demounting the floor.

The P.E. strip (65 x 10mm) consists of a recycled high density polyethylene, with semi-circular cut-outs in which the steel segments of the locking system fit.

The floor is installed over a 4mm underlay made of bonded rubber granulate.

Each panel is easily guided into position with the patented locking devices. This assures a tight fitting and level playing surface.

By positioning the panels in a correct pattern, the floor ends up as a firm and virtually seamless playing surface. The sides of the panels have tongue-and-groove fittings, the ends of the bamboo strips overlap the plywood, which guarantees a perfect fit and a constant rigidity, with no 'dead spots'.

The rubber underlay comes in rolls of 19m length by 1,60m width. The floor is finished with an approved sport finishing lacquer.

Court-markings and logo's etc. are applied before the top finish layer.



Portable flooring

### Storage:

The panels are stored onto pallets (18 x) and are numbered.

### Installation:

Only a pallet-truck and a measuring device are needed. The floor can be mounted/demounted in approx. 3 hours with a team of 4 men. The floor is supplied on pallets. The rubber rolls are supplied separately. Both ends of the floor have locking edges with integrated extensions on which the basketball backstops can be placed. These extensions have holes for the positioning pins of the portable backstops.